

# C&D TECHNOLOGIES

## Power Solutions

### GMT FUSE PANEL

**C&D TECHNOLOGIES' GMT FUSE PANEL** features compact power distribution via current-interrupting fuses. The GMT Fuse Panel accepts up to 24 GMT fuses ranging from 0.18 to 10 amperes. The GMT Fuse Panel can be used for one 60-ampere distribution capacity, or two 30-ampere A and B distribution capacities. The panel mounts in one rack space in systems with 19 or 23-inch relay racks.



111-2750-00

- UL-recognized
- Arranged for A and B distribution, 12 circuits each
- 24 or 48 volt applications
- Convenient screw terminations for wire sizes to No. 10 AWG (input) and No. 14 AWG (output) are provided on the back panel
- Form-C alarm contacts and front panel lamp

## SPECIFICATIONS

### OPERATING

Voltage: 24 or 48 Vdc  
Input Current: 60 amperes single; two group (A and B) 30 amperes each  
10 amperes per fuse maximum; not to exceed 30 amperes per group

### FUSES

Number of fuses: Up to 24  
Rating of fuses: 0.18 to 10 amperes  
Fuse type: Front-access GMT-type  
Fuse alarm: Red LED and one set of form-C contacts

### OPERATING ENVIRONMENT

Temperature: 0° to 50°C (32° to 122°F)  
Humidity: 0 to 99 percent non-condensing

### PHYSICAL

Height: 1.75 inches (4 cm)  
Depth: 8 inches (20 cm)  
Width: 19/23 inches (48/58 cm)

## GMT FUSES

| Amp Rating | Part Number |
|------------|-------------|
| 0.18       | 280-0720-00 |
| 0.25       | 280-0730-00 |
| 0.5        | 280-0700-00 |
| 0.75       | 280-0705-00 |
| 1          | 280-0710-00 |
| 1.33       | 280-0715-00 |
| 2          | 280-0735-00 |
| 3          | 280-0760-00 |
| 5          | 280-0740-00 |
| 7.5        | 280-0750-00 |
| 10         | 280-0770-00 |
| DUMMY      | 276-0002-00 |

## ORDERING INFORMATION

Order part number 111-2750-00 for each application.

Order GMT fuses as needed from the GMT fuses table.



### POWERCOM DIVISION

1400 UNION MEETING ROAD  
P.O. BOX 3053  
BLUE BELL, PA 19422-0858  
(215) 619-2700 • FAX (215) 619-7899  
(800) 543-8630  
www.cdpowercom.com

3400 EAST BRITANNIA DRIVE, SUITE 122  
TUCSON, AZ 85706  
(520) 295-4300 • FAX (520) 295-4091  
(800) 854-2456  
www.ratelco.com

Specifications are subject to change without notice. Contact your nearest C&D sales office for the latest specifications. All statements, information and data given herein are believed to be accurate and reliable but are presented without guaranty, warranty, or responsibility of any kind, express or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement, and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated, or that other measures may not be required. Unless made explicitly in writing to the customer, C&D makes no representations or warranties regarding whether any product/technology purchased and/or specifications and/or literature regarding same are the most current or advanced version thereof; and C&D assumes no obligation to inform its customers of any revisions and/or improvements to such product, technology, specifications, and/or literature.

Copyright 1998 C&D TECHNOLOGIES, INC.

# C&D TECHNOLOGIES, INC.